

chybí obrázek

Odporúčaná cena
0,00 EUR

Technické špecifikácie

vyrábané veľkosti S: 380mm / M: 420mm / L: 450mm / XL: 500mm	rám Foxy 29 Stealth Air full Carbon, Zero Suspension System, 150mm travel, Forward Geometry, aluminium CSC upper link with carbon bridge, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors. *Optional Geometry Kit.
vidlica Öhlins RXF 36 M.2 29, 160mm, TTX18 Twin Tube cartridge, tapered steerer tube, Boost 15x110mm axle, offset 44mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload, ramp chamber. Fork settings: C20 R40	hlavové zloženie Acros custom for 1-1/2
prehadzovačka Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	radenie Sram Trigger GX Eagle, 12s, X-Actuation 1:1
brzdové páčky Sram Code R, tool-free reach adjust	kľuky Sram GX Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm
stredové zloženie Sram DUB BSA, sealed bearings, 73mm	riadiidlá Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore
predstavec Onoff Sulfur FG 30mm, 6061 forged alloy, 31.8mm barbore	sedlovka Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
sedlo SDG BEL-AIR 3.0, LPU foam, steel rails	náboj predný e*thirteen Boost 15x110mm, triple-sealed, fully machined aluminum, IS 6 bolts
náboj zadný e*thirteen Boost 12x148mm, triple-sealed, fully machined aluminum w/6-degree engagement, IS 6 bolts, XD freehub	reťaz Sram NX Eagle, 12s, Powerlock
kazeta Sram XG-1275, 10-52T, 12s	drôty e*thirteen custom Hive triple-buttressed black steel, alloy nipples, nipple washers
ráfiky e*thirteen LG1 Plus Enduro, IW30 Hookless, 6069 Welded Aluminum, 30mm internal width, tubeless ready, 28 spokes	plášte Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead / Maxxis Minion DHF 29x2.5 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead
obj.c. 010.23117	gripy Onoff Desert, 1lock-on, 135mm

tlmič Öhlins TTX Air 205x65mm. Settings: high speed compression lever with climb mode, low-speed compression, rebound, air preload. Trunion top mount, 30x8mm bottom bushings	predná brzda Sram Code R, oversized 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads
zadná brzda Sram Code R, oversized 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads	nastavenia tlmiče C10 compression, R35 rebound. Volume reducers 16.000 (2xF+1E)
prevodník 32T, CNC-machined alloy, X-SYNC 2	pätka k pŕehazovačce Sram UDH
ostatné *Optional Geometry kit: steering cups: +/- 1°	