

# chybí obrázek

## Technické špecifikácie

|                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                            |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>vyrábané veľkosti</b><br>S: 380mm / M: 420mm / L: 450mm / XL: 490mm                                                                                                                                                        | <b>rám</b><br>Crafty 6061 Alloy Stealth Evo, e-Bike Optimized Zero Suspension System, 150mm travel, Forward Geometry, internal removable battery with integrated alloy cover, Boost 12x148mm rear axle, tapered head tube, one-piece Monoblock upper link, HHG internal cable routing, MAX capacity sealed bearings, oversize 17mm axles, integrated dropout speed sensor, exclusive plastic motor covers. |
| <b>vidlica</b><br>Fox 38 29 Float FIT GRIP EVOL Performance, 160mm, e-bike tuned, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload | <b>hlavové zloženie</b><br>Onoff Saturn tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41x30.2x7x45°x45°, bottom 51.9x40x8x45°x45°                                                                                                                                                                                                                                                       |
| <b>prehadzovačka</b><br>Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1                                                                                                                        | <b>radenie</b><br>Sram Trigger NX Eagle, 12s, X-Actuation 1:1, single click                                                                                                                                                                                                                                                                                                                                |
| <b>brzdové páčky</b><br>Sram G2 R, tool-free reach adjust                                                                                                                                                                     | <b>kľuky</b><br>Race Face Aeffect ebike, 165mm                                                                                                                                                                                                                                                                                                                                                             |
| <b>riadidlá</b><br>Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbare                                                                                              | <b>predstavec</b><br>Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbare                                                                                                                                                                                                                                                                                                                            |
| <b>sedlovka</b><br>Onoff Pija dropper internal, diameter 31.6mm, S size: 387x125mm, M size: 425x150mm, L/XL size: 465x170mm                                                                                                   | <b>sedlo</b><br>FIZIK Terra Aidon X5 145mm                                                                                                                                                                                                                                                                                                                                                                 |
| <b>náboj predný</b><br>Mavic, Boost 15x110mm, IS 6 bolts                                                                                                                                                                      | <b>náboj zadný</b><br>Mavic, Boost 12x148mm, ID360 Ratched system, IS 6 bolts                                                                                                                                                                                                                                                                                                                              |
| <b>reťaz</b><br>Sram SX Eagle, 12s, Powerlock                                                                                                                                                                                 | <b>kazeta</b><br>Sram PG-1210, 11-50T, 12s                                                                                                                                                                                                                                                                                                                                                                 |
| <b>drôty</b><br>Mavic J-bend duble butted, contactless lacing                                                                                                                                                                 | <b>ráfiky</b><br>Mavic E-Deemax 29, 30mm internal width, welded, PFP, tubeless ready, 28 spokes                                                                                                                                                                                                                                                                                                            |
| <b>plášte</b><br>Maxxis Minion DHF 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead, Maxxis Minion DHR II 29x2.6, tubeless ready, 3C MAXX TERRA, EXO+ Protection, 120TPI, folding bead            | <b>obj.c.</b><br>010.22220                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>gripy</b><br>Onoff Diamond, 1lock-on, 135mm                                                                                                                                                                                | <b>tlmič</b><br>Fox Float-X LV Performance, 205x65mm. Settings: compression 2 positions lever, low-speed rebound, air preload. Trunnion top mount, 25x10mm bottom bushings                                                                                                                                                                                                                                 |
| <b>predná brzda</b><br>Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads                                                                                                    | <b>zadná brzda</b><br>Sram G2 R, 4-piston caliper, Centerline 200mm IS 6 bolts one-piece rotor, steel-backed organic pads                                                                                                                                                                                                                                                                                  |
| <b>nastavenia tlmiče</b><br>medium compression, medium rebound, air volume spacer 0.2                                                                                                                                         | <b>prevodník</b><br>Sram X-Sync 2 Eagle 34T, steel, narrow-wide, 104 BCD                                                                                                                                                                                                                                                                                                                                   |

**pätka k přehazovačce**  
Mondraker M068

**motor + batérie**  
Bosch Performance Line CX Cruise (25Km/h) GEN4, Bosch Powertube  
625Wh, Bosch Kiox

---